



DEXCOWIN'S First Invented Portable XRay Device

Tube Voltage	60KV (Fixed)	
Tube current	2.0mA (Fixed)	
Focal spot	0.8mm	
Target angle	20	
Exposure	0.05 - 1.35sec (0.05 increments)	Time & Mode Control Butto
Detector	Film/Digital Sensor/PSP	LOD Windov
Power Supply	DC14.2V ~ 16.8 V (Rechargeable battery)	<u>Las vvii kov</u>
		Power Buttor
		Power Buttor













SPECIFICATIONS

Advanced Radiation Safety

- Neck strap to prevent accidents
- 1/7 Reduced radiation than other x-ray machines
- Lead wrapping the generator and cone
- Highlight Ensures both user & patient safety by reducing radiation exposure

Safety Feature Shield will protect the operator





Creative Design

- Dual exposure trigger for both hand users
- Lightweight and compact
- Takes 250 shots per fully charged battery
- Graphic UI
- Cordless, handled & portable
- Highlight Easy and convenient to use, No need for an X-ray room

Dual exposure trigger for both hand users

Composition

Main body, 2 batteries, Manual CD-ROM, Bag, Charger Sets, Certificate of Conformance, Back Scatter Shield, Neck Strap

 Economic Pakage Main body, 1 battery, Manual CD-ROM, Charger Set, Box packaging

 Optional Accessories AllMyT(stand), Wired Remote Controller, External Battery











